

INTERNAL TELEPHONES



Dictograph Sub-Station NON-LOUDSPEAKING

The Dictograph system is designed for users requiring quick and effective internal communication between not more than 15 extensions.

It is a direct-wired, a key-calling system with provision for up to two loudspeaking Master instruments. The Sub-stations employed are attractively styled in low line Afrormosia finished cabinets with strong visual appeal.

Dictograph will provide full inter communication between all the instruments, but no automatic switchboard is necessary – all calls are made and answered by a flick of the appropriate key.

For details see overleaf

Dictograph Sub-station Telephones

Dictograph System

Stock Numbers

11 Point system—

- K.258.E for single master installations
- K.259.B for double master installations

15 Point system—

- K.260.F for single master installations
- K.261 D for double master installations

Overall Dimensions

Width $9\frac{3}{4}$ "

Depth $7\frac{1}{2}$ "

Height $6\frac{3}{4}$ "

Cabinet

Finished Afrormosia, styled with a sloping face to provide easy identification of the required line.

Incoming Calls

Normally signalled by a Buzzer mounted inside the instrument. A call from a Master instrument is denoted by a distinctive signal

Outgoing Calls

To Sub-Stations—

by selecting the required extension key
followed by momentary operation of the RING key

To Master Stations—

as above but do not depress the RING key

Lamp Indication

A call from a Master Station is instantly identified by the illumination of a lamp associated with each Master instrument line.

Nameplates

Engraved to individual requirements.

Secrecy

All calls to or from a Master instrument are secret.