

# Technical Specification

## *for the UK Compact*

Description	Part Number
UK Compact Dialer	8346-001-RES 3XX
Optional PSU UK	8346-010
UK PTT Lead	8346-012
UK Subscriber Lead	8346-011

### Approvals

Approved for use in the UK, Approval Number - S/1412/3/Y/504491.

Specifications	
<b>Dimensions</b>	
Unit Size	126 x 85 x 27 mm
Unit Weight	120 g
PSU Weight	190 g
Shipping Weight	500 g
Packaging will fit through letterbox	
<b>Electrical</b>	
Optional PSU	230V +/-10%, 50mA (max)
Temperatures	0-45°C
Humidity	0-85% RH, Non Condensing
On Hook Line Voltage – 35V minimum	
Off Hook Line Current – 26mA minimum	
<b>Physical</b>	
1 Line per Unit	
Power fail safe routing to PTT if PSU used	
Line Types - Loop	
Dialling Types - MF or Loop Disconnect	
Bad Line Test Facility	
Parallel Phone Detection Circuit	

Features
<b>Remote Access</b>
Electronic Serial Number
Call Home Timer, Call Home on Install
Force Call Home Command
Routing Statistics (Peg Count)
Programming Password Protection
Central Compatible
<b>Search Facilities</b>
100+ Search Table Entries
Call Barring Capability
Cost Centre Code & VPN Ability
2 Search Table Sets
<b>Dialing Rules</b>
4 Routes for different Carriers/Call Types
Single Stage Carrier Access (CLI)
Two Stage Carrier Access (PIN)
Programmable Pause Function

# Technical Specification

## *for the EuroRoute Compact*

Description	Part Number
UK Compact Dialer	8346-001-RESXTX
Optional PSU UK	8346-010

### Approvals

Approved for use in Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, UK.

Approval Number - AA609746 (CE168X).

Specifications	
<b>Dimensions</b>	
Unit Size	126 x 85 x 27 mm
Unit Weight	120 g
PSU Weight	190 g
Shipping Weight	500 g
Packaging will fit through letterbox	
<b>Electrical</b>	
Optional PSU	230V +/-10%, 50mA (max)
Temperatures	0-45°C
Humidity	0-85% RH, Non Condensing
On Hook Line Voltage – 24V minimum	
Off Hook Line Current – 26mA minimum	
<b>Physical</b>	
1 Line per Unit	
Power fail safe routing to PTT if PSU used	
Line Types - Loop	
Dialling Types - MF or Loop Disconnect	
Bad Line Test Facility	
Parallel Phone Detection Circuit	

Features
<b>Remote Access</b>
Electronic Serial Number
Call Home Interval Timer, Call Home on Install
Force Call Home Command
Routing Statistics (Peg Count)
Programming Password Protection
Central Compatible
<b>Search Facilities</b>
200 Search Table Entries
Call Barring Capability
Cost Centre Code & VPN Ability
2 Search Table Sets
<b>Dialing Rules</b>
10 Routes for different Carriers/Call Types
Single Stage Carrier Access (CLI)
Two Stage Carrier Access (PIN)
Will Function on PBX Extension
Programmable Tone Detection
Time of Day/Day of Week Routing